



SOLUZIONE KDM

ADHESION PROMOTER
FOR MINERAL SURFACES

TECHNICAL SHEET

DESCRIPTION

SOLUZIONE KDM is an adhesion promoter for mineral surfaces glassy, glazed or unglazed, improving it considerably. It is therefore specific with the use of polyurethane, epoxy or silane adhesives. It is used to create a bonding bridge between the existing floor and the glue that you are going to apply. Compatible with adhesives: **VISEDIL KE 22, VISEDIL KE 20, VISEDIL K18, VISEDIL K10, VISEDIL SM1.**

TECHNICAL DATA

Appearance: clear colorless liquid
 Viscosity Ford n°4: 12 sec.
 Minimum application temperature: +12 °C
 Specific weight: 0,87 Kg / L
 Pot Life: n.a.
 Waiting time before applying the glue: 10-15 min. at 25 °C

INDICATIONS

1. Do not associate the product with water-based systems.
2. Ventilate the area during application of the product.
3. For handling the product wear gloves and appropriate glasses.

For any questions about changes to operations, contact your technical service.

SURFACE PREPARATION

The surfaces to be treated must be free of dust, mold release agents or other extraneous materials.

PRODUCT PREPARATION

The product is ready for use

APPLICATION

Apply directly **SOLUZIONE KDM** on the surface to be treated in a thin layer with the aid of a brush or soaked cloth, avoiding stagnation of material.

AVERAGE COVERAGE WITH BRUSH

20-30 gr / sqm. with the use of a flat brush (depends on the conditions of the installation surface).

STORAGE

The product keeps the warranty in its original packaging (not altered) under standard conditions (15-35 °C and 35-70% RH) for a period of 12 months. It is important to keep the product in a dry and ventilated area away from heat and direct sunlight.

PACKAGING

ME drum 1,0 Lt. (30 pcs. box)

**SOLUZIONE KDM**
ADHESION PROMOTER
FOR MINERAL SURFACES**TECHNICAL SHEET****NOTE**

The information contained in this data sheet is based on our best knowledge and preparation.

However, this cannot be interpreted as a commitment to guarantee, since the means, place of employment and the application conditions are beyond our control. So we do not assume any liability for unauthorized use of the product as the advice given in this application is indicative. In the case where there is any doubt about the application, it is recommended to perform preliminary tests.

The company Viscol s.n.c. therefore reserves the right to change or update this sheet without notice.

Users of the product are advised to check that you have the latest update.

BEFORE USING THE PRODUCT ALWAYS CONSULT MATERIAL SAFETY DATA SHEETS